


Submittal: DWPSB0612B



STRONG-POINT[®] PHILLIPS BUGLE HEAD, FINE THREAD, PHOSPHATE COATING

Size	Part#	Case Qty.	Description
6 x 3/4	606	15M	Phillips Bugle Head, Fine Thread, Phosphate Coating
6 x 1	610	10M	Phillips Bugle Head, Fine Thread, Phosphate Coating
6 x 1-1/8	611	10M	Phillips Bugle Head, Fine Thread, Phosphate Coating
6 x 1-1/4	614	8M	Phillips Bugle Head, Fine Thread, Phosphate Coating
6 x 1-1/2	612	6M	Phillips Bugle Head, Fine Thread, Phosphate Coating
6 x 1-5/8	615	5M	Phillips Bugle Head, Fine Thread, Phosphate Coating
6 x 1-3/4	616	4M	Phillips Bugle Head, Fine Thread, Phosphate Coating
6 x 2	620	3.5M	Phillips Bugle Head, Fine Thread, Phosphate Coating
6 x 2-1/4	624	3M	Phillips Bugle Head, Fine Thread, Phosphate Coating

Application: Attaches gypsum board to light gauge steel.

- Specifications:**
- Meets ASTM¹ A 510 for carbon steel manufacturing
 - Meets ASTM C 1002 for attaching gypsum board to steel studs

- Features:**
- Type 'S' point for fastening gypsum to light gauge steel

Installation: A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.

¹(American Society of Testing Materials)