


Submittal: SDDPM0808B



STRONG-POINT[®] PHILLIPS MODIFIED TRUSS (R/W) HEAD, BLACK OXIDE

Size	Part#	Pt.	Case Qty.	Description
8-18 x 1/2	M82B	2	10M	Phillips Modified Truss (R/W) Head, Black Oxide
8-18 x 3/4	M83B	2	8M	Phillips Modified Truss (R/W) Head, Black Oxide
8-18 x 1	M84B	2	5M	Phillips Modified Truss (R/W) Head, Black Oxide
8-18 x 1-1/4	M85B	2	5M	Phillips Modified Truss (R/W) Head, Black Oxide

Application: Attaches wire lath to metal studs.
Drill Capacity (in.): .035 - .100

- Specifications:
- Meets ASTM¹ C 1513 for cold-formed steel framing connections
 - Meets ASTM A 510 for carbon steel manufacturing
 - Manufactured to SAE² J78 for dimensional specifications
 - Meets F.I.P.³-1000.7 for torsional strength and drill speed

Installation: A standard screw gun with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. Do not over torque as it can cause the head to snap or stripping of the recess. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

Pullout Values (Avg. Lbs.)									
Fastener		Steel Gauge							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
8-18	2	260	292	479	685	933	1533		

Shear Values (Avg. Lbs.)									
Fastener		Steel Gauge (Lapped)							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
8-18	2	546	721	1031	1049				

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

¹(American Society of Testing Materials)

²(Society of Automotive Engineers)

³(Fastener Inspection Products)