


Submittal: DWPMB0809B**STRONG-POINT[®] PHILLIPS MODIFIED TRUSS (R/W) HEAD, K-LATH, BLACK OXIDE COATED**

Size	Part#	Case Qty.	Description
8 x 9/16	85MB	10M	Phillips Modified Truss (R/W) Head, K-Lath, Black Oxide Coated
8 x 3/4	86MB	8M	Phillips Modified Truss (R/W) Head, K-Lath, Black Oxide Coated
8 x 1	88MB	5M	Phillips Modified Truss (R/W) Head, K-Lath, Black Oxide Coated
8 x 1-1/4	89MB	5M	Phillips Modified Truss (R/W) Head, K-Lath, Black Oxide Coated
8 x 1-5/8	90MB	4M	Phillips Modified Truss (R/W) Head, K-Lath, Black Oxide Coated

Application: Multipurpose sheet metal screw for light gauge metal or wood applications.
Finishing screw for use when aesthetics are important.

Specifications: • Meets ASTM¹ A 510 for carbon steel manufacturing

Installation: A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced Phillips Drive bit. Do not over torque as it can cause the head to snap or damage to the work surface.

¹(American Society of Testing Materials)