



Submittal: NPSHZ10085Z



$\operatorname{STRONG-POINT}^{^{(\!\!\!\!\!\!\!\!\!\!\!\!)}}$ slotted indented hex washer head, zinc plated

Size	Part#	Case Qty.	Description
10 x 1/2	N10085	10M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 3/4	N10125	8M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 1	N10165	5M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 1-1/2	N10245	3M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 2	N10325	2M	Slotted Indented Hex Washer Head, Zinc Plated
Application:	Attaches light gauge sheet metal to sheet metal or wood.		
Specifications:	 Meets ASTM¹ A 510 for carbon steel manufacturing 		
	Meets ASTM B 633 for electrodeposited zinc coatings		
	Meets ASTM F1941 for corrosion resistance		
Features:	Multipurpose sheet metal screw for light to medium gauge applications		
	• 22° point pierces light gauge metal		
	• Twin fast thread design creates faster installation speeds		
Installation:	A 5/16" hex nut setter or 5/16" drive socket with torque limiting nose piece set at a minimum of 1400 RPM drive speed recommended.		
	Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of three		
	full threads beyond the metal structure.		

¹(American Society of Testing Materials)

N10085_N10325_Rev. A (7/7/15)