


Submittal: DWPCD0616D



STRONG-POINT[®] PHILLIPS BUGLE HEAD, COARSE THREAD, DACROTIZED[®]

Size	Part#	Case Qty.	Description
6 x 1	610CD	10M	Phillips Bugle Head, Coarse Thread, Dacrotized
6 x 1-1/4	614CD	8M	Phillips Bugle Head, Coarse Thread, Dacrotized
6 x 1-5/8	615CD	5M	Phillips Bugle Head, Coarse Thread, Dacrotized
6 x 2	620CD	3.5M	Phillips Bugle Head, Coarse Thread, Dacrotized
6 x 2-1/4	624CD	3M	Phillips Bugle Head, Coarse Thread, Dacrotized

Application: Exterior wood screws for outdoor applications.
Attaches wood to wood.

Specifications:

- Meets ASTM¹ A 510 for carbon steel manufacturing
- Product meets ASTM B-117 for salt spray corrosion testing

Features:

- Dacrotized coating exceeds 500/hr. salt spray resistance

Coating: The Dacrotized coating is an immersion zinc flake/chromate dispersion coating with medium corrosion protection.

Installation: A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.

¹(American Society of Testing Materials)