



Submittal: DWPCY0840Y





$\textbf{STRONG-POINT}^{\texttt{®}} \textbf{ PHILLIPS BUGLE HEAD, COARSE THREAD, ZINC YELLOW}$

Size	Part#	Case Qty.	Description
8 x 2-1/2	822CY	2.5M	Phillips Bugle Head, Coarse Thread, Zinc Yellow
8 x 3	830CY	2M	Phillips Bugle Head, Coarse Thread, Zinc Yellow
Application:	Multi-purpose screw for interior or outdoor applications.		
	Attaches gypsum board or wood to wood.		
Specifications:	Meets ASTM ¹ A 510 for carbon steel manufacturing		
	Product meets ASTM B-117 for salt spray corrosion testing		
Features:	• 90/hr. salt spray resistance		
	Used in low corrosion applications		
Coating:	The Zinc Yellow coating prevents the oxidation of steel by forming a protective barrier.		
Installation:	A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced		
	Phillips drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque		
	as it can cause the head to snap or damage to the work surface.		

¹(American Society of Testing Materials)

822CY_830CY_Rev. A (7/8/15)