

**Submittal:** DSSTLT7ZY1056**STRONG-POINT<sup>®</sup> STAR DRIVE FLAT HEAD w/NIBS, TYPE '17', ZINC YELLOW**

| Size       | Part#   | Case Qty. | Description   |
|------------|---------|-----------|---|
| 10 x 3-1/2 | XT1031Y | 1M        | Star Drive Flat Head w/Nibs, Type '17', Zinc Yellow |
| 10 x 4     | XT1040Y | .8M       | Star Drive Flat Head w/Nibs, Type '17', Zinc Yellow |

Application: For interior or outdoor applications.  
Attaches wood to wood.

Specifications:

- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
- Product meets ASTM B-117 for salt spray corrosion testing

Features:

- Yellow Zinc coating exceeds 180/hr. salt spray resistance
- .0003 plating thickness
- Star Drive prevents cam out and stripping for improved driveability
- Type '17' reduces wood splitting and eliminates the need for pre-drilling
- Nibs under head provide flush finish
- Used in low corrosion applications

Coating: The Zinc Yellow coating prevents the oxidation of steel by forming a protective barrier.

Installation: A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a T-25 Star drive bit. Do not over torque as it can cause the head to snap or damage to the work surface.

<sup>1</sup>(American Society of Testing Materials)