



Submittal: WWPBSQF0940L



$\textbf{STRONG-POINT}^{\texttt{®}} \textbf{ SQUARE DRIVE FLAT HEAD PARTICAL BOARD SCREWS}, \textbf{ PLAIN AND LUBED}$

Size	Part#	Case Qty.	Description
9 x 2-1/2	940QL	2.5M	Square Drive Flat Head Partical Board Screws, Plain and Lubed
9 x 3	948QL	2M	Square Drive Flat Head Partical Board Screws, Plain and Lubed
Application:	Wood screws for interior wood applications. Cabinet work and furniture assembly.		
Specifications:	 Meets ASTM¹ A 510 for carbon steel manufacturing Product meets ASTM B-117 for salt spray corrosion testing 		
Features:	 Asymmetrical thread pattern Resists material slippage during pull out and vibration Square drive prevents cam out and stripping Superior holding power 		
Installation:	A standard screw oun with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. Use a #2 reduced		

mstanation:

A standard screw gun with torque limiting nose piece set at a maximum of 2500 KPM drive speed recommended. Use a #2 reduced Square drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.