


**Submittal:** ELAG1448P




**STRONG-POINT<sup>®</sup> ACOUSTICAL EYE LAG, SHARP POINT, PLAIN**

Size	Part#	Case Qty.	Description
1/4 x 3	EA3	1M	Acoustical Eye Lag, Sharp Point, Plain
1/4 x 4	EA4	1M	Acoustical Eye Lag, Sharp Point, Plain
1/4 x 5	EA5	1M	Acoustical Eye Lag, Sharp Point, Plain

**Application:** Attaches drop ceiling tie wires to wood.

- Specifications:**
- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
  - Product meets ASTM B-117 for salt spray corrosion testing

**Installation:** An acoustical eye lag bit with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of 3/4" into the wood structure.



Pullout Values (Lbs.)								
Fastener	2 x 4 Wood Block							
Size	Test 1	Test 2	Test 3	Test 4	Test 5	Test 6	Test 7	Average
1/4	1124	1221	1105	1176	1202	1143	1197	1166

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.