

STRONG-POINT[®] Get the Point. Strong-Point.

Submittal: WWPBSQFNX0940Z

STRONG-POINT[®] SQUARE DRIVE FLAT HEAD w/NIBS, PARTICLE BOARD SCREWS, TYPE '17', ZINC PLATED

| Size | Part# | Case Qty. | Description |
|-----------------|---|--------------|--|
| 9 x 2-1/2 | XQ940NZ | 2.5M | Square Drive Flat Head w/Nibs, Particle Board Screws, Type '17', Zinc Plated |
| 9 x 3 | XQ948NZ | 2M | Square Drive Flat Head w/Nibs, Particle Board Screws, Type '17', Zinc Plated |
| Application: | Wood screw for interior wood applications. | | |
| | Attaches wood to wood. | | |
| Specifications: | • Meets ASTM ¹ A 510 for carbon steel manufacturing | | |
| | Meets ASTM B 633 for electrodeposited zinc coatings | | |
| | Meets ASTM F1941 for corrosion resistance | | |
| Features: | • Type '17' reduces wood splitting and eliminates the need for pre-drilling | | |
| | Square drive prevents cam out and stripping | | |
| | Nibs under head provide flush finish | | |
| | Asymmetrical thread pattern | | |
| | Superior h | olding power | |
| Coating: | The Zinc coating prevents oxidation of steel by forming a protective barrier. | | |
| Installation: | A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced | | |
| | Square drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque | | |
| | as it can cause the head to snap or damage to the work surface. | | |

¹(American Society of Testing Materials)

XQ940NZ_XQ948NZ_Rev. A (2/24/16)