


Submittal: SDUHW45SSC1214



STRONG-POINT[®] UNSLOTTED INDENTED HEX WASHER HEAD, STRONG-SHIELD COATED

Size	Part#	Pt.	Case Qty.	Description
12-24 x 7/8	H4C	4	4M	Unslotted Indented Hex Washer Head, Strong-Shield Coated

Application: Attaches metal to metal.
Drill Capacity (in.): .125 - .250

- Specifications:
- Meets ASTM¹ C 1513 for cold-formed steel framing connections
 - Meets ASTM A 510 for carbon steel manufacturing
 - Manufactured to SAE² J78 for dimensional specifications
 - Meets F.I.P.³-1000.7 for torsional strength and drill speed
 - Rust/Acid Rain Protection
 - ACQ Compatible
 - Exceeds 1,000/hrs. salt spray resistance



Installation: A 5/16" hex nut setter or 5/16" drive socket with torque limiting nose piece set at a maximum of 1500 RPM drive speed recommended. Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

Pullout Values (Avg. Lbs.)										
Fastener		Steel Gauge								
Size	Pt.	22	20	18	16	14	12	1/8	3/16	1/4
12-24	4			484	679	959	1489	2371	3384	3732

Shear Values (Avg. Lbs.)										
Fastener		Steel Gauge (Lapped)								
Size	Pt.	22	20	18	16	14	12	1/8	3/16	1/4
12-24	4						1989	1972		

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

¹(American Society of Testing Materials)

²(Society of Automotive Engineers)

³(Fastener Inspection Products)